

No.	Qty.	Object	Unit Price EURO	Amount EURO
			<b>Carry over:</b>	
		<p><b><u>Protective Coating for Submersible Motor Mixers</u></b>                      2-component tar-epoxy resin protective paint, e.g. Inertol Poxitar or equivalent.</p> <p><u>Consisting of:</u>                      Preparatory treatment (sand blasting and degreasing) according to instructions of the manufacturer:.</p> <p style="padding-left: 40px;">1.coats: 50 µ Zinc dust on epoxy resin basis                      2. - 4.coats: each 100 µ coating varnish</p> <p style="padding-left: 40px;">Minimum film thickness: 0.35 mm                      Colour: black</p> <p><b><u>Lowering Frame, free standing:</u></b>                      for the stationary installation of the previously mentioned submersible motor mixer. Fastening the guide rails only on the tank floor. Reaction forces directed in such wise that the guide rails are almost completely load-free and all forces are directed to the floor.</p> <p>Installation depth: m</p> <p><u>consisting of :</u>                      Guide rail (square rail): 100 x 100 x mm                      Designed as complete system.                      With appropriate floor fastening and all fixing hardware.                      Installation position and alignment are defined by the bidder.</p> <p style="padding-left: 40px;">Material: 1.4301 / 1.4571</p> <p><b><u>Lifting Equipment, dismantable:</u></b>                      Auxiliary lifting equipment according to VBG8, designed as smooth working, slewable lifting equipment to serve above-mentioned submersible motor mixers for mobile application.</p> <p style="padding-left: 40px;">Carrying capacity: kN</p> <p><u>Material:</u>                      Lifting equipment: .....                      Rope: 1.4401 .....                      Rope pulleys: .....                      Fastening elements: .....</p> <p>For the individual assemblies the individual weight of 40 kg may not be exceeded.</p> <p><b><u>Locating Unit for Lifting Equipment:</u></b>                      incl. complete fastening materials,                      designed for wall/floor installation (as per requirement)</p> <p style="padding-left: 40px;">Material: galvanized St / 1.4301 / Al .....</p>		
			<b>Amount</b>	