

Hygienic Pump

Vitastage

Type Series Booklet



Legal information/Copyright

Type Series Booklet Vitastage

All rights reserved. The contents provided herein must neither be distributed, copied, reproduced, edited or processed for any other purpose, nor otherwise transmitted, published or made available to a third party without the manufacturer's express written consent.

Subject to technical modification without prior notice.

© KSB SE & Co. KGaA, Frankenthal 15/05/2020


Contents

Hygienic Pump	4
Sterile Process Pumps in Close-coupled Design	4
Vitastage.....	4
Main applications.....	4
Fluids handled	4
Operating data.....	4
Designation	4
Design details	4
Materials.....	4
Certifications	4
Connections.....	5
Technical details.....	5
Characteristic curves.....	6
Dimensions	7
Pump accessories.....	10

Hygienic Pump

Sterile Process Pumps in Close-coupled Design

Vitastage



Main applications

- Food and beverage industry
- Chemical industry
- Further industrial applications with moderate hygienic requirements

Fluids handled

- Pure liquids not mechanically or chemically aggressive to the pump

Operating data

Operating properties

Characteristic	Value
Flow rate	Q [m³/h] ≤ 12,5
Head	H [m] ≤ 150
Operating pressure	p [bar] ≤ 16
Fluid temperature	T [°C] ≤ 140 (higher on request)

Designation

Example: Vitastage 10/3/75 2 B T

Designation key

Code	Description
Vitastage	Type series
10	Size
3	Number of stages
75	Motor rating (7.5 kW × 10)
2	Number of poles
B	Installation type
T	Seal design

Design details

Design

- Standard design with materials to Regulation (EC) No. 1935/2004

Design

- High-pressure centrifugal pump
- Casing in ring-section design
- Multistage

Installation

- Horizontal/vertical installation

Impeller type

- Closed radial impeller with multiply curved vanes

Shaft seal

- Standardised mechanical seal to EN 12756 (⇒ Page 5)

Drive

- Self-cooling IEC squirrel cage motor
- Winding 50 Hz, 230 V/400 V up to 4 kW
- Winding 50 Hz, 400 V/690 V from 5.5 kW
- Type of construction B5/B35
- IP55 enclosure
- Thermal class F
- Other motors on request

Materials

Component	Material
Pump casing	1.4408/1.4401 (AISI 316)
Impeller/diffuser	1.4401 (AISI 316)
Impeller nut	1.4401 (AISI 316)
Welle	1.4401 (AISI 316)
Motor housing	Aluminium/Cast iron
Motor shroud	1.4301 (AISI 304)
Connections	1.4408 (AISI 316)
Installation parts	1.4301 (AISI 304)

Certifications

Overview

Label	Effective in:	Note
	All countries	Certified quality management to ISO 9001
	All countries	Elastomers FDA, 3A, USP class VI certified

Connections

Horizontal installation

- Axial suction nozzle
- Tangential discharge nozzle

Vertical installation

- Horizontal suction nozzle
- Tangential discharge nozzle

Types of connection

- Threaded connection to DIN 11851
- Threaded connection to SMS standard
- Other connection types on request

Technical details

Mechanical seal design

Mechanical seal material, elastomers, static sealing elements


Description	Material
Mechanical seal (single internal mechanical seal)	SiC/CARB/EPDM ¹⁾ , SiC/TUC/EPDM, SiC/SiC/EPDM
Elastomers	EPDM ¹⁾ , FPM, FFPM, PTFE
Static sealing elements	EPDM ¹⁾ , NBR, FPM, FFPM, FEP

Key

Code	Material
CARB	Graphite
EPDM	Ethylene propylene diene rubber
TUC	Tungsten carbide
SiC	Silicon carbide
NBR	Nitrile rubber
FPM	Fluoroelastomer (Viton)
FFPM	Perfluoroelastomer
PTFE	Polytetrafluoroelastomer
FEP	Fluorocarbon (PTFE-encapsulated silicone)

1) Standard design

Characteristic curves



Dimensions

Horizontal installation – version without motor shroud




Fig. 1: Vitastage 05 without motor shroud

Dimensions

Size	P	DN _s	DN _m	ØA	B	C	D	E	F	G	K	H	J	I	L	M	N	O	Y	[kg]
	[kW]	[mm]																		
05/1	1,1	32	25	162	155	118	100	9	56	314	370	90	240	150	125	150	8	9,5	66,5	18
05/2	1,5	32	25	181	182	143	100	12,5	80	314	394	90	240	150	140	165	10	10	66,5	21
05/3	2,2	32	25	181	206	143	100	12,5	104	337	441	90	240	150	140	165	10	10	66,5	28
05/4	3,0	32	25	202	236	176	140	13	128	337	465	90	240	150	160	196	12	12	66,5	43

Horizontal installation – version with motor shroud




Fig. 2: Vitastage 05 with motor shroud

Dimensions

Size	P	DN _a	DN _m	ØA	B	D	F	G	H	I	K	J	M	Y	[kg]
	[kW]	[mm]													
05/1	1,1	32	25	238,5	92	230	56	395	178	150	451	315	136,5	66,5	22
05/2	1,5	32	25	238,5	118	230	80	395	178	150	477	315	136,5	66,5	25
05/3	2,2	32	25	238,5	140	230	104	395	178	150	499	315	136,5	66,5	32
05/4	3,0	32	25	238,5	164	230	128	395	178	150	523	315	136,5	66,5	48

Vertical installation





Fig. 3: Vitastage 05, vertical installation, discharge nozzle position

a	Discharge nozzle 270°
b	Discharge nozzle 0°/360°
c	Discharge nozzle 90°
d	Discharge nozzle 180°

Dimensions

Size	P	DN _a	DN _m	ØA	F	G	H	I	J	K	Y	[kg]
	[kW]	[mm]										
05/1	1,1	32	25	220	69	316	71	150	136	456	65	19
05/2	1,5	32	25	220	93	316	71	150	136	480	65	22
05/3	2,2	32	25	220	117	346	71	150	136	534	65	29
05/4	3,0	32	25	220	141	346	71	150	136	558	65	40
05/5	4,0	32	25	220	165	371	71	150	136	607	65	42
05/6	4,0	32	25	220	189	371	71	150	136	631	65	43
05/7	5,5	32	25	220	213	386	71	150	136	670	65	55
05/8	5,5	32	25	220	237	386	71	150	136	694	65	56

Motor feet



Motor foot dimensions [mm]

Motor size (IEC-DIN)	p [kW]		A	B	C	D	E	F	G	H
	2-pole	4-pole								
71	0,37; 0,55	0,25; 0,37	110	90	150	190	10	10	40	40
80	0,75; 1,1	0,55; 0,75	130	100	170	210	10	10	40	40
90 S	1,5	1,1	160	100	200	240	10	10	40	40
90 L	2,2	1,5	160	125	200	240	10	10	40	40
100 L	3	3	180	140	230	280	12	12	50	50
112 M	4	4	180	140	230	280	12	12	50	50
132 S	5,5; 7,5	5,5	226	140	266	346	12	12	60	60
132 M	-	7,5	226	178	266	346	12	12	60	60
160 M	11; 15	11	310	210	330	400	14	14	50	50
160 L	18,5	15	310	254	330	400	14	14	50	50
180 M	22	18,5	328	241	387	448	15	15	60	60
180 L	-	22	328	279	387	448	15	15	60	60

Pump accessories

- Stainless steel motor shroud
- Mounted on a trolley, with switch and power cable
- Vertically adjustable ball feet



KSB SE & Co. KGaA
Johann-Klein-Straße 9 • 67227 Frankenthal (Germany)
Tel. +49 6233 86-0
www.ksb.com