

## DeltaSolo – Fully Automatic Pressure Booster System



DeltaSolo SVP



### Applications:

- Irrigation systems and rainwater harvesting system
- Service water supply systems for trade and industry

### More information:

[www.ksb.com/products](http://www.ksb.com/products)



DeltaSolo MVP

# DeltaSolo – Fully Automatic Pressure Booster System

## Energy-efficient

- KSB SuPremE® IE5\* synchronous reluctance motors (only for variant DeltaSolo SVP)
- Energy-efficient operation and constant pressure ensured by speed control

## Suitable for drinking water

System and components certified to the corresponding national drinking water standards

## Handling

Easy and fast commissioning of ready-to-connect, pre-assembled and tested system

## Long service life

Corrosion resistance provided by powder-coated base-plate and stainless steel hydraulic components

## Reliable and safe



- Integrated dry running protection for reliable operation
- Zero dead volume in piping and optimum flushing of add-on parts provide protection against legionella.

Technische Daten	MVP	SVP
Q [m³/h]	Up to 22	Up to 76
H [m]	Up to 108	Up to 145
P [bar]	Up to 16	Up to 16
T [°C]	Up to 60	Up to 60
Max. motor rating [kW]	Up to 2.2	Up to 22.0

\*Efficiency classes to IEC TS 60034-30-2:2016

## Pump characteristic curves

For a better overview only some pressure classes are shown; further pressure classes are available as standard.



KSB SE & Co. KGaA  
Johann-Klein-Straße 9  
67227 Frankenthal (Germany)  
www.ksb.com