



Project:

Project No.:

| Cons. No. | Quantity | Item  | Unit price | Total |
|-----------|----------|---|------------|-------|
|           |          | <p><b>KSB Standard pump MegaCPK</b><br/>Pump comprises:</p> <p>Single-stage volute casing pump to DIN EN ISO 2858 / ISO 5199, GB/T 5656 - Chinese Standard is identical with ISO 5199:2002, horizontal, in back pull-out design, bearing bracket with support foot, pump feet cast-on at casing. Axial suction nozzle, discharge nozzle pointing upwards, with replaceable shaft protection sleeve.</p> <p>Volute casing: Grey cast iron/.....<br/>Impeller: Grey cast iron/.....<br/>Bearing bracket: Ductile cast iron, with oil-lubricated bearings<br/>Shaft: Steel/.....<br/>Shaft protection sleeve: Shaft sealing depending<br/>Shaft sealing: Gland packing *) / Mechanical seal *)</p> <p>Fluid handled: .....<br/>Minimum flow rate: .....<br/>Operating temperature: ..... °C<br/>Density: ..... kg/dm<sup>3</sup><br/>Viscosity: ..... mm<sup>2</sup>/s<br/>Flow rate: ..... m<sup>3</sup>/h<br/>Develop head: ..... m<br/>NPSH pump: ..... m<br/>Inlet nominal pressure: ..... bar<br/>Pump final pressure: ..... bar<br/>Power absorbed pump: ..... kW<br/>Speed: ..... 1/min<br/>Suction nozzle: DN ..... PN .....<br/>Discharge nozzle: DN ..... PN .....<br/>Flange design: EN Standard version *) / Nut to EN *) / ASME Class 150 drilled *) / ASME Class 125 drilled *)<br/>Weight: ..... kg<br/>Make: KSB</p> <p style="text-align: right;"><b>Pump price:</b></p> <p><b>KSB Standard pump MegaCPK</b><br/>Pump set comprises:</p> <p>Single-stage volute casing pump to EN 22858/ISO 2858/ ISO 5199, GB/T 5656 - Chinese Standard is identical with ISO 5199:2002, horizontal, in back pull-out design, bearing bracket with support foot, pump feet cast-on at casing. Axial suction nozzle, discharge nozzle pointing upwards, with replaceable shaft protection sleeve.</p> <p>Volute casing: Grey cast iron/.....<br/>Impeller: Grey cast iron /.....<br/>Bearing bracket: Ductile cast iron, with oil-lubricated bearings<br/>Shaft: Steel/.....<br/>Shaft protection sleeve: Shaft sealing depending<br/>Paint: RAL 5002 *) / other<br/>Shaft sealing: Gland packing *) / Mechanical seal *)<br/>If mechanical seal::<br/>Manufacturer: .....<br/>Typ: .....<br/>Material: .....<br/>Installation: .....</p> |            |       |
|           |          | Carry forward   |            |       |

\*) Delete as applicable

Project:

Project No.:

| Cons. No. | Quantity | Item  | Unit price | Total |
|-----------|----------|---|------------|-------|
|           |          | <p>Fluid handled: .....</p> <p>Minimum flow rate: .....</p> <p>Operating temperature: ..... °C</p> <p>Density: ..... kg/dm<sup>3</sup></p> <p>Viscosity: ..... mm<sup>2</sup>/s</p> <p>Flow rate: ..... m<sup>3</sup>/h</p> <p>Develop head: ..... m</p> <p>NPSH pump: ..... m</p> <p>Inlet nominal pressure: ..... bar</p> <p>Power absorbed pump: ..... kW</p> <p>Speed: ..... 1/min</p> <p>Suction nozzle: DN ..... PN .....</p> <p>Discharge nozzle: DN ..... PN .....</p> <p>Flange design: EN Standard version *) / Nut to EN *) / ASME Class 150 drilled *) / ASME Class 125 drilled *)</p> <p>Weight: ..... kg</p> <p>Make: KSB</p> <p style="text-align: right;"><b>Pump price:</b></p> <p><b>Base plate</b> including alignment material.<br/>Design: Steel *) / Grey cast iron *)</p> <p><b>Flexible shaft coupling</b> with / without *) spacer sleeve, with contact guard to EN 294.<br/>Coupling guard treadable: Steel *) / Brass *)</p> <p><b>Three-phase current-aquirell-cage motor</b>, European make, B3 construction type, Type of enclosure IP 55, thermal class F<br/>Motor winding: 220-240 V / 380-420 V *, 50 Hz<br/>380-420 V / 660-725 V *, 50 Hz</p> <p>Starting method: d.o.l. / star-delta *)</p> <p>Motor rating: ..... kW</p> <p>Weight of drive train: ..... kg</p> <p>EX-protection: with *) / without *)</p> <p>Energy effizienz: IE2</p> <p><b>Foundation bolts:</b> with *) without *)</p> <p style="text-align: right;"><b>Accessories price:</b></p> <p style="text-align: right;"><b>Pump set comprises price:</b></p> |            |       |
|           |          | Carry forward   |            |       |

\*) Delete as applicable