

BOA-H Mat E / Mat P – Shut-off Valve with Actuator



BOA-H Mat E

Applications:

- General industrial facilities
- Process engineering
- Plant engineering
- Cooling circuits
- Heating systems

More information:

www.ksb.com/products



BOA-H Mat P

Your contact:



BOA-H Mat E / Mat P – Shut-off Valve with Actuator

1 Versatile use

Optimal opening thanks to the standard throttling valve plug up to DN 100. Plug with soft seat for special applications optionally available.

2 Reduced maintenance costs

Thanks to the replaceable valve plug. Instead of changing the complete upper section, only the valve plug is replaced, if necessary.

3 Optimised tightness

Valve with fully confined bonnet gasket and either maintenance-free PTFE V-rings with spring or high-temperature resistant graphite gland packing.

4 Wide range of actuators

State-of-the-art electric and pneumatic actuators with a large variety of accessories.

Variants

Plug with soft seat

High-temperature resistant paint (grey aluminium)

Special flange designs

Similar type series

BOA-CVE H

BOA-CVP H

BOA-CVE Compact

BOA-CVE SuperCompact


BOA-CVE Control IMS

BOA-CVE Compact EKB

BOA-CVE W

BOA-H

Available nominal diameters:
DN 20 to DN 150



Pressure/temperature ratings

Nominal pressure	Material	Permissible operating pressures in bar at a temperature of °C ¹⁾				
		-10 to +120	+200	+250	+300	+350
PN16	EN-GJS-400-18-LT	16	14.7	13.9	12.8	11.2
PN25	EN-GJS-400-18-LT	25	23	21.8	20	17.5

¹⁾ Intermediate temperatures can be derived by linear interpolation.

The limits given in the technical codes must be complied with. Please contact us for details.



KSB Aktiengesellschaft
Johann-Klein-Straße 9
67227 Frankenthal (Germany)
www.ksb.com