

SISTO-16HWA:

Short text:

Soft-seated flanged shut-off valve, diaphragm valve, flange in accordance with DIN EN 1092-2, PN 16, body and bonnet made of 5.1301 (EN GJL-250), enclosed diaphragm made of EPDM, temperature limit max. 140°C

Manufacturer/Type: SISTO Armaturen S.A./SISTO-16HWA

Pressure class: PN 16
Nominal size: DN 15-200

Long text:

Soft-seated flanged shut-off valve, diaphragm valve in straight-way pattern, maintenance-free, flange in accordance with DIN EN 1092-2, PN 16, body and bonnet made of 5.1301 (EN GJL-250), enclosed diaphragm made of EPDM, spiral supported, suitable for drinking water and hot water temperature limit max. 140°C, with rising handwheel, position indicator with integrated stem protection, manufactured and tested according to EN 13397, marked in accordance with DIN EN 19 (ISO 5209)

Manufacturer/Type: SISTO Armaturen S.A./SISTO-16HWA

Pressure class: PN 16
Nominal size: DN 15-200

Variants:

with electric actuators,
with pneumatic actuators,
with limit switches,
with locking device,
with chain wheel,
with leakage detection hole and additional stem seal,
with lead-sealable cap (prevents unauthorised actuation)
or
stem extension

Typical tender for SISTO-16HWA

8635.522/01-10

Subject to technical modification without prior notice

01.04.2020