

BOA-Compact EKB:

Short text:

Soft-seated globe valve with flanged ends, face-to-face length to EN 558/14, single-piece body made of EN-GJL-250, with handwheel, throttling plug, position indicator, locking device, travel stop; with internal and external electrostatic plastic coating (EKB), DVGW-approved according to DIN 3546-1 for drinking water

Manufacturer/type: KSB/BOA-Compact EKB

Pressure class: PN 10/16
Nominal size: DN 15 - 200

Long text:

Soft-seated globe valve with flanged ends, single-piece body made of EN-GJL-250, face-to-face length to EN 558/14; with handwheel, throttling plug, position indicator above the handwheel, locking device, protected internal travel stop, with internal and external electrostatic plastic coating (EKB), DVGW-approved according to DIN 3546-1 for drinking water, maintenance-free, -10 to 80 °C, straight-way valve in slanted seat design, non-rotating stem made of 1.4021 with protected, external thread, stem sealed by EPDM profile ring; with compact, fully EPDM-encapsulated throttling plug providing soft main and back seat, non-rising handwheel; designed, manufactured, tested and marked in acc. with the European Pressure Equipment Directive.

Manufacturer/type: KSB/BOA-Compact EKB

Pressure class: PN 10/16
Nominal size: DN 15 - 200

Variants:

with lead-sealable cap (prevents unauthorised actuation) as assembly set
or
with electric actuator

Typical tender for BOA-Compact EKB

7112.522/02-EN

Subject to technical modification without prior notice

16.06.2020