

BOA-SuperCompact:

Short text:

Soft-seated wafer-type globe valve, single-piece body made of EN-GJL-250, face-to-face length of DN 20-150 to EN 558/94 (DN 200 PN 6 or PN 16: face-to-face length see BOA-Compact), with handwheel, with flange alignment holes corresponding to flange thickness to DIN EN 1092 and full bolt hole pattern; with throttling plug, position indicator, locking device, travel stop and insulating cap with anti-condensation feature

Manufacturer/type: **KSB/BOA-SuperCompact**

Pressure class:	PN 6/10/16	DN 200 PN 6 or PN 16
Nominal size:	DN 20-150 (200)	DN 200 with flanged ends (type BOA-Compact)

Long text:

Soft-seated wafer-type globe valve, single-piece body made of EN-GJL-250, face-to-face length to EN 558/94, with handwheel, with flange alignment holes corresponding to flange thickness to DIN EN 1092 and full bolt hole pattern for PN 6 to 16 for centring and downstream dismantling, fully suitable for dead-end service; straight-way valve in slanted seat design, with throttling plug, position indicator, locking device, protected internal travel stop and insulating cap with anti-condensation feature; compact, fully EPDM-encapsulated throttling plug providing soft main and back seat, stem sealed by EPDM profile ring, maintenance-free, -10 to 120 °C; suitable for full insulation in acc. with German heating system regulations (HeizAnIV); non-rotating stem made of 1.4021 with protected, external thread; with blue exterior coating (similar to RAL 5002); designed, manufactured, tested and marked in acc. with the European Pressure Equipment Directive.

Manufacturer/type: **KSB/BOA-SuperCompact**

Pressure class:	PN 6/10/16	DN 200 PN 6 or PN 16
Nominal size:	DN 20-150 (200)	DN 200 with flanged ends (type BOA-Compact)

Variants:

with lead-sealable cap (prevents unauthorised actuation) as assembly set
or
with electric actuator

Typical tender for BOA-SuperCompact

7113.521/01-EN

Subject to technical modification without prior notice

23 April 2018