

SISTO-16RGA:

Short text:

Soft-seated shut-off valve with threaded sleeve,
diaphragm valve with internal thread designed for drinking water,
internal thread in accordance with DIN EN 10226-1 (ISO 7/1), PN 16,
body made of gunmetal,
bonnet made of POM DN 15-20 and 5.1301 (EN GJL-250)/PA(Rilsan) DN 25-80,
diaphragm made of EPDM/W270, enclosed, temperature limit max. 90°C

Manufacturer/Type: SISTO Armaturen S.A./SISTO-16RGA

Pressure class: PN 16
Nominal size: Rp ½" – Rp3"

DVGW / SVGW / Belgaqua

Long text:

Soft-seated shut-off valve with threaded sleeve in straight-way pattern,
diaphragm valve with internal thread for drinking water, maintenance-free,
internal thread in accordance with DIN EN 10226-1 (ISO 7/1), PN 16,
body made of gunmetal, bonnet made of POM for DN 15-20 and 5.1301 (EN GJL-250),
coated with PA (Rilsan) for DN 25-80,
diaphragm made of EPDM (W270) in accordance with the recommendations by the
German Environment Agency and hygienically harmless, enclosed, spiral-supported,
suitable for drinking water temperature limit max. 90°C,
with rising handwheel, position indicator with integrated stem protection,
manufactured and tested according to EN 13397,
marked in accordance with DIN EN 19 (ISO 5209)

Manufacturer/Type: SISTO Armaturen S.A./SISTO-16RGA

Pressure class: PN 16
Nominal size: Rp ½" – Rp3"

DVGW / SVGW / Belgaqua

Typical tender for SISTO-16RGA

7112.525/01-DE

Subject to technical modification without prior notice

04.12.2019